



Características Generales

Cubiertas			Espesor (mm)	Peso		Seccion_ cm2	Mom. Inercia I (cm4)	Fachadas		
Mom Max m.kg	Mom.Re sistente Wx(cm3)	Mom.Iner cia Reduci. lx (cm4)		Kg/m	Kg/m2			Mom.Iner cia Reduci. lx (cm4)	Mom.Re sistente Wx(cm3)	Mom Max m.kg
43,460	3,104	7,066	0.5	3,93	4.7	5.98	7,236	6,729	2,924	40.94
53,420	3,816	8,669	0.6	4.71	5.64	7.17	8,655	8,391	3,666	51.31
62,460	4,461	10,158	0.7	5.5	6.58	8.37	10,158	10,034	4,394	61.52
71,280	5,091	11,625	0.8	6.25	7.52	9.56	11,625	11,609	5,082	71.15
88,820	6,344	14,569	1.0	7.86	9.4	11.96	14,569	14,570	6,345	88.82
110,610	7,980	18,270	1.2	9.42	11.25	15.0	18,270	18,270	7,901	110.6
132,220	9,444	21,991	1.5	11.78	14.1	18.75	21,991	21,991	9,445	132.23
Valores sujetos a cambio sin previo aviso										



Sobrecargas Admisibles (Kg/m2)

SOBRECARGA PARA CARGAS UNIFORMEMENTE REPARTIDAS (kg/m2) PARA DOS APOYOS																
Distancia entre apoyos (m) POSICION CUBIERTA								Esp. (mm)	Distancia entre apoyos (m) POSICION FACHADA							
4,5	4	3,5	3	2,5	2	1,5	1,0		1,0	1,5	2	2,5	3	3,5	4	4,5
17.17	20.5	26.7	36.4	52.4	81.9	145.5	347.6	0.5	327.4	136.9	77.0	49.3	34.2	25.2	19.3	16.2
21.1	25.7	33.5	45.6	65.7	102.6	182.5	427.3	0.6	410.4	168.9	94.9	60.8	42.2	31.0	23.7	20.2
24.67	30.8	40.2	54.7	78.7	123.0	218.7	499.6	0.7	492.1	201.3	113.2	72.5	50.3	37.0	28.3	24.3
28.16	35.6	46.5	63.2	91.1	142.3	253.0	570.2	0.8	569.2	234.2	131.7	84.3	58.6	43.0	32.9	28.1
35.09	44.4	58.7	79.1	113.7	177.6	315.8	710.5	1.0	710.5	300.9	169.3	108.3	75.2	55.3	42.3	35.1
43.7	55.3	72.2	98.3	141.6	221.2	393.3	888.3	1.2	884.8	385.1	216.6	138.6	96.3	70.7	54.2	43.7
53.23	66.1	86.4	117.5	169.3	264.5	470.1	1057.7	1.5	1057.8	469.4	264.0	169.0	117.3	86.2	66.0	52.2
Valores sujetos a cambio sin previo aviso																

SOBRECARGA PARA CARGAS UNIFORMEMENTE REPARTIDAS (kg/m2) PARA CUATRO APOYOS																
Distancia entre apoyos (m) POSICION CUBIERTA								Esp. (mm)	Distancia entre apoyos (m) POSICION FACHADA							
4,5	4	3,5	3	2,5	2	1,5	1,0		1,0	1,5	2	2,5	3	3,5	4	4,5
21.4	24.1	31.4	42.8	61.6	96.3	171.2	434.6	0.5	409.3	181.9	102.3	65.5	45.5	33.4	25.6	20.2
21.4	24.1	31.4	42.8	61.6	96.3	171.2	434.6	0.5	409.3	181.9	102.3	65.5	45.5	33.4	25.6	20.2
26.4	29.7	38.8	52.7	76.4	118.7	211.3	534.6	0.6	513.1	228.1	123.8	81.2	57.0	41.1	32.2	25.3
30.8	35.0	46.2	62.9	90.6	141.5	251.6	624.6	0.7	515.2	273.4	153.8	98.4	68.4	50.2	38.4	30.4
35.2	41.2	53.8	73.2	105.4	164.7	292.8	712.8	0.8	711.5	316.2	177.9	113.8	79.1	58.1	44.6	35.1
43.8	52.0	69.1	94.7	135.0	210.5	373.0	910.8	1.0	888.3	394.6	221.8	140.0	98.7	72.2	55.5	43.8
54.6	67.7	85.4	120.3	173.3	270.8	481.0	1106.10	1,0	1106.4	491.6	276.5	177.7	122.5	90.3	69.1	54.6
65.3	82.5	107.8	146.7	211.2	330.0	585.7	1322.20	2,0	1322.3	587.7	330.1	211.6	146.9	107.9	82.6	65.3
Valores sujetos a cambio sin previo aviso																